

VERTICAL MAILBOXES

6000 SERIES

Front Loading Recessed and Surface Mount Installation

Frames and doors are extruded aluminum and the 7" deep compartments are 24 ga. Steel. Doors are 5 1/2" w and 16" h and have concealed hinges. Each door is equipped with a 5 pin cylinder cam lock (1000 changes) and 2 keys. The front of each door has a 2 1/2" w x 5/8" h indentation that will accommodate a pressure sensitive label (included) for the tenant name and /or box number. Modules are available with 3 to 7 compartments and come in surface mount and fully recessed models. The surface mount model can be semi recessed with the addition of a trim kit to cover the rough wall opening. Modules are completely assembled for easy installation and are prepped for postal access locks to be installed by local postal authority. All compartments are usable for incoming mail. Units can be customized. Consult our sales staff for assistance with modifications to meet your needs.

OPTIONS

- Integral directory
- Surface mount directory
- Double wide doors
- Outgoing mail slot
- Trim kit
- Private access locks

Finishes

- Clear anodized aluminum
- Gold powder coat
- Silver powder coat
- Bronze powder coat

Identification

- Window/card holders
- Engraved plastic adhesive tabs
- Black filled engraving



R 6003

Security's vertical mailboxes are designed and constructed for trouble-free use and durability.



S 6007

Postal Service regulations require the installation of a tenant name directory in all multi-dwelling buildings having 15 or more mail receptacles. The separately mounted directory, either vertical or horizontal configuration, will accommodate 40 or 80 names which are embossed on 1/4" label tape (not included). Available in clear anodized finish, or silver/gold/bronze powder coating.



DV40, 6 1/2" W x 18 3/4" H
DV80, 10 1/4" W x 18 3/4" H



C/B 6001/6002

- Surface or recessed
- Aluminum construction
- Heavy-duty extruded 5/32" thick aluminum door
- Extruded frame and trim
- Clear anodized (recess) or silver, gold, bronze powder
- Product C/B 6001 Mail collected from the front. Full hinged door prepared for U.S.P.S. lock
- Product C/B 6002 Private cam lock with 2 keys for private use

FRAME SIZE

18 3/4" H x 18 7/8" W x 7 1/2" D (Surface)
18 23/32" H x 15 3/4" W x 6 3/4" D (Recessed)

COMPARTMENT SIZE

16 1/2" H x 16 1/2" W x 7 1/2" D (Surface)
17 3/16" H x 14 1/8" W x 6 3/4" D (Recessed)

SLOT SIZE

3/4" H x 11" W

VERTICAL MAILBOX INSTALLATION

10550/SEC
BuyLine 3545

- No more than two tiers may be installed.
- Boxes must be arranged in groups.
- Under one postal lock, the maximum number of boxes is 7 and the minimum is 3.

RECESSED MOUNTED INSTALLATION

The diagram illustrates the recessed mounting of a mailbox unit into a wall. It shows a side view with dimensions: overall height of 60", a depth of 36 1/2" from the finished floor to the top of the unit, and a depth of 18 1/4" from the wall to the front of the unit. A front view shows the unit's width (W) and rough opening (R.O.). A detail view shows the unit's depth of 7 1/2" and a height of 18 7/8" for the compartment area.

Number of Doors	Rough Opening Width
3	17 1/4"
4	22 3/4"
5	28 1/4"
6	33 3/4"
7	39 1/4"

All Modules Are
18 7/8" High Overall
7 1/2" Deep Overall
17 1/4" High Rough Opening

Each Box Compartment is:
5 1/2" W x 16" H x 7" D

SURFACE MOUNTED INSTALLATION

The diagram illustrates the surface mounting of a mailbox unit to a wall. It shows a side view with dimensions: overall height of 60", a depth of 7 1/2" from the finished floor to the front of the unit, and a depth of 38" NET from the wall to the front of the unit. A front view shows the unit's width (WIDTH). A detail view shows the compartment being mounted to the wall with mounting screws.

Number of Boxes	Overall Width
3	18 3/4"
4	24 1/4"
5	29 3/4"
6	35 1/4"
7	40 3/4"

All Modules Are
18 7/8" High Overall
7 1/2" Deep Overall

Each Box Compartment is:
5 1/2" W x 16" H x 7" D

1. Mount assembly to wall with #10 x 1 1/2" mounting screws.
2. Insert compartment.

Complete installation instructions, including all U.S. Postal Service regulations, come with each module.